

# Manually self-assembling the lift



Scan the  
QR code &  
watch the  
instruction  
video




## Practical guidelines when setting up

- Always use gloves when setting up.
- Climbing the ladder and standing on the furniture platform is prohibited.
- During installation, always keep the cable taut so that the safety retains contact with the motor.
- Always connect the plugs of both the remote control and automatic stop.
- The maximum platform weight is 200 kg per lifting operation.
- Only use the lift on a stable surface.
- Always raise the lift by the ladder and never by the carriage.

## Wind the spool properly

Make sure the **spool is always taut during winding**.  
Make sure the coil does not get caught between the spool and side plate. Incorrect winding causes a lot of damage to the lift.



## Rules of thumb

- The wheels must not touch the ground when using the lift
- Place the ladder at a maximum of 3 metres distance from the wall at an angle of approx. 70°
- Always secure the ladder at the top and brace it with a pipe for support



Scan the QR code & watch the instruction video



## Setting up the ladder lift

**1** Secure the auto-stop contact just above or below the top step of the ladder with a clamp. Only hand tighten and secure it on the **right-hand side** (when standing in front of the ladder).

**2** Raise the ladder with head section (cable wheel) and install the auto-stop using the provided rope.

**3 4** Add ladders from the bottom to obtain the desired height. Add the motor last.

**5** Fasten the ladders together using the provided bolts. Always place the eye of the bolts on the outside (only hand tighten). Secure the ladder at the top with a tension strap (e.g. to a radiator or balcony). This is to prevent the lift from tipping over.

**6** Make sure you connect the electric plugs of the power supply, remote control, and emergency stop.

**7 8 9** Use the remote control to activate the cable (with hook) and allow it to run anticlockwise around the wheel on the top ladder back to the carriage.

**IMPORTANT:** Always keep the cable taut during installation AND attach the cable to the carriage **under** the curved bar. The cables must not cross each other and must run parallel to each other.

**10 11** Secure the furniture platform/box on the carriage and make sure it is level. Secure all platform pins with cotter pins.

**12** If needed, attach side guards to the furniture platform/box.

**13** You must install a pipe for support when you will use the ladder lift for a second or third floor, or when lifting more than 100 kg. It is best to place it just above the middle of the ladder.

**14** Use the remote control to operate the furniture platform/box.

## Dismantling the ladder lift

- Always use work gloves when dismantling.
- Take the furniture platform/box off the carriage.
- Disconnect the cable from the carriage and rewind it using the remote control.
- Always keep the cable slightly taut while continuing to guide the cable.
- Attach the hook of the cable to the spring on the motor. Do not tighten it.
- Disconnect electrical wires.
- Dismantle and remove each of the ladder pieces starting at the bottom.